

PUSH-IN FITTINGS Nickel-Plated Brass

Specifications	Fluid type	Air (No other gases or liquids)
	Working pressure	0-150PSI / 0-9.9Kgf/cm ² (0-990kPa)
	Negative pressure	-29.5inHg / -750mmHg(-750Torr)
	Working temperature	32-140F / 0-60C

PUSH-IN FITTINGS Nickel-Plated Brass

“YC”

MPC-G
Male Straight



MODEL (tube-thread)	
4-01	10-01
4-02	10-02
6-02	10-03
6-03	10-04
6-04	12-02
8-01	12-03
8-02	12-04
8-03	14-03
8-04	

MPL-G
Male Elbow



MODEL (tube-thread)	
4-01	8-04
4-02	10-01
6-02	10-02
6-03	10-03
6-04	10-04
8-01	12-02
8-02	12-03
8-03	12-04

MPB-G
Male Branch Tee



MODEL (tube-thread)	
4-01	8-04
4-02	10-01
6-02	10-02
6-03	10-03
6-04	10-04
8-01	12-02
8-02	12-03
8-03	12-04

MSL-G
Speed control



MODEL (tube-thread)	
4-01	8-04
4-02	10-01
6-01	10-02
6-02	10-03
6-03	10-04
6-04	12-02
8-01	12-03
8-02	12-04
8-03	

MPGJ Plug-In Reducer



MODEL (tube1-tube2)	
6-4	10-8
8-4	12-10
8-6	12-8
10-6	

MPM Bulkhead Union



MODEL (tube)
4
6
8
10
12

MPE Union Tee



MODEL (tube)
4
6
8
10
12

MPU Union Straight



MODEL (tube)
4
6
8
10
12